



SLIDETRAX™ ADJUSTABLE TIE DOWNS - SET OF 4 - INSTALLATION INSTRUCTIONS

The installation of additional SlideTrax Tie Downs allows paddlers added opportunity to custom outfit their kayaks. Easily installed and positioned, additional tie downs can be used to secure or position outfitting components to make your kayak all the more personal.

Contents of Kit

- 4 Tie Down Assemblies
 - Base plates
 - Hexhead mounting screws
 - Tie down fittings

Tools Required

- 4.5mm or 3/16" Hex head wrench
- Straight edge screwdriver

INSTALLATION INSTRUCTIONS:

1. Remove the base plate from the tie down assembly and insert into end of SlideTrax rail.
2. Move to desired position. Use straight edge screwdriver to push the base plate to desired location.
3. Insert mounting screw through top of molded fitting.
4. Align fitting so that bottom of fitting aligns with top of SlideTrax rail. If you examine the base of the fitting you will note that it is cut away on base on two sides so that the top or side mounted tie down opening is oriented inboard or outboard on the rail.
5. Position fitting over base inserted into rail and drive screw into threaded hole in base using hex head wrench.
6. Tighten firmly to maintain position. To adjust position, loosen mounting screw just enough to allow the assembly to slide along the rail. Retighten when in desired position.